



# ANTI-FOAM

## Defoamer

### PRODUCT DESCRIPTION & BENEFITS

**ANTI-FOAM** is a specially formulated product used to kill foam on contact. It is designed to be sucked up through the vacuum hose of a hot water extractor, or sprayed into the recovery opening of a direct hook-up water rinser or extractor. May also be used to eliminate foam in auto scrubber / wet dry vacuums.

#### BENEFITS:

- Effective Against A Broad Range of Foam Sources
- Does Not Form Residue

### DETAILED USAGE & INSTRUCTIONS

It is recommended that protective gloves and eyewear be worn when using this product.

**DIRECTIONS:** Shake well before using. Whenever excess foaming is encountered -during extraction, mix 2 oz. of ANTI-FOAM to 12 oz. of water in a separate container and suck up through the vacuum hose while the machine is running. The container should be used only for this purpose. This will enable the hose to become coated with the defoamer and begin to eliminate the foam before it gets to the recovery tank. ANTI-FOAM is a very effective product, but the usage may need to be increased if there is excessive suds build-up in the carpeting. Add ANTI-FOAM to recovery tank of auto scrubber / wet dry vacuum or self containment extractor.

Refer to the product label or contact a Cynamic Chemical Co. professional for additional usage instructions.

#### TECHNICAL SPECIFICATIONS

Appearance / Color .....Viscous Liquid  
Odor .....Neutral  
Shelf Life .....2 years  
Solubility in Water .....Complete  
Foaming .....None  
pH .....7.5 ± 0.005  
Specific Gravity .....1.09 ± 0.005  
Storage Temperature.....45-110 °F

#### FEATURES & BENEFITS

- Does Not Form Residue
- Effective Against a Broad Range of Foam Sources

003244

**CYNAMIC**  
CHEMICAL COMPANY

1472 Louis Bork Drive  
Batavia, IL 60510