



# COURT APPROVED

## Waterless Cleaner

### PRODUCT DESCRIPTION & BENEFITS

Use **COURT APPROVED** on wood floors, cabinets, and woodwork. Other applications include use as a cleanup/tacking solvent for oil modified urethanes, and solvent penetrating seals. COURT APPROVED helps to restore the shine on the surface cleaned. It leaves no oil or film to dull or fade. It is not harmful to most solvent based finish surfaces.

### RECOMMENDED USES:

- Wood Floors Cleaning and Tacking
- Tar, Asphalt Solvent
- Woodwork Cleaning

**DO NOT DILUTE.** Dry Screening Procedures for Wood Floors: Floor must be dry before screening floor with #100, #120 or #150 grit screens following MFMA guidelines for coating. Once screening procedure is completed, vacuum and tack floor with COURT APPROVED to remove fine dust particles. Continue STEP 2 until floor is completely dust free. Inspect floor for uniformity and any unscreened patches. Allow floor to thoroughly dry before applying Court System Oil Modified Urethane Wood Coatings.

### DETAILED USAGE & INSTRUCTIONS

**Solvent Scrub Procedures for Wood Floors:** Dust mop floor thoroughly. Remove all water soluble soil by damp mopping with COURT APPOINTED following label directions. Apply COURT APPROVED with a mop, to an area approximately 100 square feet. Scrub using a 175 RPM, single disc floor machine equipped with stripping pad or 100 grit screen. ADD PRODUCT AS NECESSARY TO KEEP FROM DRYING. Squeegee solution and pick-up with mops or towels. DO NOT USE ELECTRICAL MACHINES FOR PICK-UP. Rinse with a clean solution and pick-up. Continue to other areas and repeat procedure. Tack rag floor with COURT APPROVED. Allow floor to thoroughly dry before applying Court System Oil Modified Urethane Wood Coatings. Coverage for tacking: 900-1000 sq.ft/gal.

**Cabinets, Woodwork, Doors, etc.:** Apply product with a clean cloth. Scrub heavily soiled and marked areas with scrubbing pad. Wipe dry with a clean cloth.

**NOTE:** Do not use on solvent sensitive surfaces such as asphalt or rubber tile, plastics, etc.

Refer to the product label or contact a Cynamic Chemical Co. professional for additional usage instructions.

### TECHNICAL SPECIFICATIONS

Appearance / Color .....	Colorless
Odor.....	Solvent, Banana
Shelf Life .....	2 years
Foaming .....	None
Solubility in Water .....	Complete
Specific Gravity .....	0.772 ± 0.005
Storage Temperature.....	45-110 °F

### FEATURES & BENEFITS

- Free Flowing Liquid
- Cleans and Restores
- Wide Variety of Uses
- No Residue on Evaporation

002450

**CYNAMIC**  
CHEMICAL COMPANY

1472 Louis Bork Drive  
Batavia, IL 60510