



# COURT JUSTICE

## Wood Floor Finish (2 Part)

### PRODUCT DESCRIPTION & BENEFITS

**COURT JUSTICE** is a crosslinked, water based, 100% aliphatic urethane wood coating which exhibits exceptional durability and gloss. Floor preparation and product application can be accomplished in one day.

**RECOMMENDED USES:** • Use on All Hardwood Floors, Gymnasiums/Sports Floors, Parquet, Commercial/Institutional/Residential Floors

### DETAILED USAGE & INSTRUCTIONS

**NEWLY SANDED PREVIOUSLY FINISHED FLOORS:** (1) Apply one coat of COURT SEAL or COURT SECURITY with a K100 E-Z Way Applicator and lambs wool pad or lightweight bar. Allow to dry tack free and abrade with a 120 grit screen and tack with towel dampened with COURT APPROVED and let dry. (2) Repeat step 1. (3) Install game lines if needed. Use a water based enamel following directions on container. (Test paint for compatibility.) (4) Using a mechanical mixer, stir COURT JUSTICE until vortex is formed and slowly add crosslinker. Stir for 4 or 5 minutes. To crosslink less than the full contents, use 2 oz. of crosslinker for each gallon of product. Both COURT JUSTICE and crosslinker containers are calibrated for accurate measurement. It is important that the crosslinker be added as it contributes greatly to the water resistance, durability and adhesion of the finish. (5) Apply four coats of COURT JUSTICE using a K100 E-Z Way Applicator or lightweight bar at the rate of 600 sq. ft. per gallon.

**RECOATING PREVIOUSLY FINISHED FLOORS:** (1) Clean floor with COURT APPOINTED Wood Floor Prep Cleaner following label instructions. Do not over wet floor. (2) Abrade entire floor with 120 grit screens. Use each side of screen for approximately 200 sq. ft. Vacuum and tack with clean towel and water. (3) Using a mechanical mixer, stir COURT JUSTICE until a vortex is formed and slowly add crosslinker. Stir for 4 or 5 minutes. (4) Apply one coat of COURT JUSTICE using a K100 E-Z Way Applicator or lightweight bar at the rate of 600 sq. ft. per gallon. Let dry until tack free 4-6 hours under normal conditions. (5) Apply second coat of COURT JUSTICE.

**NOTE:** Do not apply more than 2 coats of COURT JUSTICE per day. Allow each coat to dry until tack free before applying next coat. If more than 16 hours elapse between coats, abrade surface with a 120 grit screen or 3M maroon pad. Vacuum and tack rag. All crosslinked finish must be used within 24 hours. Discard unused product after this time. For best results do not apply this product when temperature exceeds 90°F and humidity 80%. Do not apply over a catalyzed water based epoxy without applying COURT SEAL first. Let product cure 48 hours with good ventilation before heavy traffic. Do not use over water based floor finishes, shellac, lacquer or coatings and seals containing stearates, waxes or silicones. Do not abrade floor using steel wool as particles remaining on floor will rust when COURT JUSTICE is applied. Adhesive masking tape and decals may cause delamination of coating when removed.

**MAINTENANCE:** Dust mop frequently with a mop treated with COURT AUTHORIZED Water Based Dust Mop Treatment. Do not use a freshly treated mop or retreat a soiled mop. Damp mop weekly or more often if needed with COURT APPOINTED Wood Floor Prep Cleaner. To restore gloss, high speed burnish with at least a 1500 rpm machine and 3M High Speed Burnishing Hair Pad. To assist in enhancing gloss apply RESTORE ORDER High Speed Restorer.

**SPECIAL INSTRUCTIONS:** It is important that the crosslinker be added as it contributes greatly to the water resistance, durability and adhesion of the finish. Do not apply over a catalyzed water based epoxy.

Refer to the product label or contact a Cynamic Chemical Co. professional for additional usage instructions.

### TECHNICAL SPECIFICATIONS

Appearance / Color .....	Translucent
Odor .....	None
Shelf Life .....	2 years
Solubility in Water .....	Complete
V.O.C.....	265 gm/l
Leveling .....	Excellent
Coverage.....	600-700 sq. ft./gal.
Dry Time .....	4-6 hours
Specific Gravity .....	1.032 ± 0.005
Storage Temperature.....	45-110 °F

### FEATURES & BENEFITS

- Non-Powdering, Non-Yellowing
- Easy Application and Simple Maintenance
- Outstanding Durability

002423

**CYNAMIC**  
CHEMICAL COMPANY

1472 Louis Bork Drive  
Batavia, IL 60510