



COURT SEAL

Water Based Wood Sealer

PRODUCT DESCRIPTION & BENEFITS

COURT SEAL is a water based acrylic wood seal to be used in conjunction with HIGH COURT and COURT JUSTICE. Key film properties are short dry time, very slight grain raising, and excellent sand screening characteristics. Wood floors sealed with COURT SEAL provide a solid base to be top coated with HIGH COURT, HIGH COURT 25, AQUA COAT, COURT JUSTICE or COURT SECURITY. Coverage is 750 sq. ft./gal.

RECOMMENDED USES:

- Gymnasiums/Sports Floors
- Parquet Floors
- Commercial/Institutional/Residential Floors

DETAILED USAGE & INSTRUCTIONS

- (1) Apply one coat of COURT SEAL with a K100 E-Z Way Applicator and lambs wool pad or lightweight bar.
- (2) Let dry tack free and abrade with 120 grit screen to remove raised grain and dull gloss. Vacuum to remove dust and tack with towels dampened with water.
- (3) Apply second coat of COURT SEAL following steps 1 and 2.
- (4) Install game lines if needed. Use water based enamel following directions on container. Test paint for compatibility.
- (5) Apply four coats of HIGH COURT, COURT JUSTICE, or COURT SECURITY following label directions.

Refer to the product label or contact a Cynamic Chemical Co. professional for additional usage instructions.

TECHNICAL SPECIFICATIONS

Appearance / Color	Opaque
Odor	Slight Amine
Shelf Life	2 years
Solubility in Water	Complete
Foaming	None
Coverage	750 sq. ft./gal.
pH	8.5 ± 0.5
Specific Gravity	1.031 ± 0.005
Storage Temperature.....	45-110 °F

FEATURES & BENEFITS

- Non-Flammable
- Easy Clean Up
- Non-Yellowing
- Excellent Screening Properties
- Quick Dry

002425

CYNAMIC
CHEMICAL COMPANY

1472 Louis Bork Drive
Batavia, IL 60510