



# CRETE SEAL

## Water Based Concrete Sealer

### PRODUCT DESCRIPTION & BENEFITS

Crete Seal represents recent enhancements in acrylic, non-metallic floor coatings. Its combination of special straight linked polymers is formulated to keep commercial, institutional and industrial concrete floors bright and attractive at the lowest possible cost. It reduces the need for stripping and sealing and for the application of more top coats of finish. This seal is trouble-free in application. It levels smoothly without streaks and dries to a clear, hard tough shine. Crete Seal is self-sealing, filling pores and providing a protective coating for concrete floors. Crete Seal will not yellow or dull the original beauty of floors.

### DETAILED USAGE & INSTRUCTIONS

**Floor Preparation:** For proper results, the floor must be thoroughly scrubbed with Pepco SQK and properly rinsed before application.

**Application:** Use a high quality clean mop or K100 E-Z Way Applicator.

**Number Of Coats:** The porosity of the floor should be filled until a smooth even surface is obtained. The number of coats depends on porosity of the floor and desired appearance.

**Maintenance:** Dust mop daily with Water Based Dust Mop Treatment. Damp mop daily or as needed to keep floor clean and bright.

**Special Instructions:** In some instances, due to discoloring or peeling of previous seals/finishes, it will be necessary to remove prior coatings before applying Crete Seal. In these cases, strip old coatings, rinse floor thoroughly at least twice and let floor dry completely. Floor is now ready to be coated with Crete Seal.

Refer to the product label or contact a Cynamic Chemical Co. professional for additional usage instructions.

### TECHNICAL SPECIFICATIONS

Appearance / Color.....White  
Odor.....Amine  
Shelf Life .....2 years  
Solubility in Water .....Complete  
Specific Gravity .....1.031 ± 0.005  
Storage Temperature.....45-110 °F  
V.O.C.....0gm./l.  
Gloss.....91 min  
Zinc Content .....0%  
Dry Time.....25-35 min.  
Coverage.....1000-1500 sq.ft/gal.

### FEATURES & BENEFITS

- Water/Detergent Resistant
- Easy Application
- Spray Buffable
- Brilliant Clear Gloss
- Rapid Recoatability
- Zinc-Free

002518

**CYNAMIC**  
CHEMICAL COMPANY

1472 Louis Bork Drive  
Batavia, IL 60510