



# ORANGE DEGREASER

## Citrus Base Cleaner

### PRODUCT DESCRIPTION & BENEFITS

**ORANGE DEGREASER** is an organic citrus extract based cleaner that tackles really big jobs from smelly dumpsters to greasy auto service bays. Foams away grease and grime naturally without harsh acids, petroleum based, or alkaline solvents. Natural organic citrus is an excellent cleaner and a natural deodorizer that eliminates the most persistent odors and leaves a lingering fresh scent.

### DETAILED USAGE & INSTRUCTIONS

**DIRECTIONS FOR USE:** Cover all electrical outlets. Remove gross soil from surfaces and equipment. Attach GUN II to Gilmer hose sprayer quick connect. Attach APM #10 Orange Degreaser cartridge to GUN II. Apply hot foam liberally to all washable surfaces including floors, walls, tables, etc. Allow foam to cling to surface at least 5 minutes. Remove GUN II from sprayer nozzle and rinse thoroughly. Let surface drain dry. Do not wipe dry. Tilt movable surfaces to aid water run-off. To sanitize surfaces: Spray with EPA registered APM #6 NO RINSE SANITIZER following directions on the container. Leave surfaces tilted until equipment is put back in use.

**PROCEDURE:** Apply by mop, spray or other suitable means, such as sponge or cloth. Allow Orange Degreaser to penetrate soil. Then scrub with floor machine or manually with brush or sponge. Pick up foam. (On floors, use squeegee and wet dry vac, or mop foam into bucket of clear water. Excessive foam in the wet dry vac can be controlled by anti-foams.) Then, rinse with hot water spray.

**NOTE:** Wear rubber or plastic gloves for manual cleaning. Metal surfaces should be rinsed immediately.

**Dispensed System Operating Procedures:** Turn on water source to wall mount unit. Uncap the reload cartridge. Firmly place one hand on top of the wall mount dispenser holding the cartridge from the bottom, push it up into the wall mount dispenser until the cartridge locks into place. Check that the cartridge is securely in place by pulling down gently. Turn wall mount valve to "ON" position. Fill to desired container level. TO UNLOAD WALL MOUNT: Make sure wall mount unit valve is in the "OFF" position. Place one hand under the existing reload cartridge and press the red "To Release Cartridge Press" button and allow the cartridge to drop down into your hand. Place the cap back on cartridge and put back into storage rack. If cartridge is empty, discard according to local, state and federal regulations. Shut off water source to wall mount unit.

Refer to the product label or contact a Cynamic Chemical Co. professional for additional usage instructions.

### TECHNICAL SPECIFICATIONS

Appearance / Color .....Amber  
Odor.....Citrus  
Shelf Life .....2 years  
Solubility in Water .....Complete  
Foaming.....High  
pH .....12.8 ± 0.3  
Specific Gravity .....0.954 ± 0.005  
Storage Temperature .....45-90 °F

### FEATURES & BENEFITS

- Natural Citrus Base
- Refreshing Scent
- Ideal for Trash Receptacles, Kennels, Auto Bays and Engines

001615

**CYNAMIC**  
CHEMICAL COMPANY

1472 Louis Bork Drive  
Batavia, IL 60510