



PIPEDOWN

Drain/Grease Trap Treatment

PRODUCT DESCRIPTION & BENEFITS

This natural decomposition of soils and waste helps eliminate drain and sewer line problems when used as directed in a regular program. PIPE DOWN is safe, easy-to-use and requires no special equipment. Semi-viscous formula clings and promotes “dwell time” on vertical surfaces for improved retention and performance. Eliminates odor. Keeps drains open. Liquifies waste. Protect from freezing: Store at temperatures above 32°F and below 120°F. Do Not use in conjunction with bleach, disinfectants or drain chemicals.

DETAILED USAGE & INSTRUCTIONS

DIRECTIONS FOR USE: Apply during the period of lowest flow. Treat the lowest levels of a system first to prevent blockage by materials released from higher levels. GREASE TRAPS: Begin treatment after pumping. Hand clean thick mats. For clean-up, add 1 quart of product per 25 cubic ft. capacity (190 gals.) daily until odor and mat are gone. For maintenance, add 5 oz. of product per 26 cubic ft. capacity daily.

DRAIN AND DOWN PIPES: For clean-up, apply daily for one week. For maintenance, apply 2 to 4 times per week. May be used after a sulfuric acid drain opener if the system is flushed completely. Rate of application: Use 2 oz. per 2 in. of pipe diameter. Note: Not intended for emergency use in opening totally clogged drains.

SEPTIC TANKS—HOME SYSTEM: Apply 8 oz. monthly. Institutions: Apply 8 oz. for every 12 people using the system weekly. Apply by pouring into toilet and flushing. If the system is clogged or odorous, double the amount used and treat daily until flow improves and/or odor is controlled.

PORT-A-TOILETS AND PIT TOILETS: apply 1 to 1 1/2 gallon along with enough water to cover solids. Maintain with 4 to 16 oz. weekly. Re-treat after pumping with 1/2 to 1 gallon of product. Do not add disinfectants or other chemicals.

RECREATIONAL VEHICLES AND OTHER HOLDING TANKS: Initially add 3 oz. per gallon of water in the tank. Maintain with 1 oz. per day.

WALLMOUNT OPERATING PROCEDURES: TO LOAD WALL MOUNT: Turn on water source to wallmount unit. Uncap the reload cartridge. Firmly place one hand on top of the wall mount dispenser. Holding the APM cartridge from the bottom, push it UP into the APM wallmount dispenser until the cartridge locks into place. Let go of the APM cartridge. Check that the APM cartridge is securely in place by pulling down gently. Turn wallmount valve to “ON” position. Fill to desired container level. TO UNLOAD WALL MOUNT: Make sure wall mount unit valve is in the “OFF” position. Place one hand under the existing reload cartridge and press the red “To Release Cartridge Press” button and allow the APM cartridge to drop down into your hand. Place the cap back on cartridge and put back into storage rack. If cartridge is empty, discard according to local, state and federal regulations. Shut off water source to wall mount unit.

Refer to the product label or contact a Cynamic Chemical Co. professional for additional usage instructions.

TECHNICAL SPECIFICATIONS

Appearance / ColorWhite
Odor.....Fresh Scent
Shelf Life2 years
Solubility in WaterComplete
FoamingNone
pH7.0 ± 0.05
Specific Gravity0.1 ± 0.005
Storage Temperature.....45-110 °F

FEATURES & BENEFITS

- Non-Corrosive
- Natural and Biodegradable
- Will Not Harm Plumbing
- Eliminates Odors
- Ideal For Food Processing Areas, Restaurants, Restrooms, and Kitchens

001604

CYNAMIC
CHEMICAL COMPANY

1472 Louis Bork Drive
Batavia, IL 60510